

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 95.25, Waist: 78.75, Hips: 102.75
Pattern Name: -

Notes

How to print Printing

Once your Calibration Test Page has been printed, measure the 4"x 4" (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.



Pattern Name: -

Seam Allowance: 1 (3/8 in)

Pattern pieces:


1. "CENTER FRONT", MAIN FABRIC: Cut 2
2. "SIDE FRONT", MAIN FABRIC: Cut 2
3. "CENTER BACK", MAIN FABRIC: Cut 1
4. "SIDE BACK", MAIN FABRIC: Cut 2
5. "SLEEVE", MAIN FABRIC: Cut 2
6. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
7. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
8. "COLLAR STAND", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
9. "WELT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
10. "INNER POCKET BAG", LINING: Cut 2
11. "OUTER POCKET BAG", MAIN FABRIC: Cut 2








Pattern Specs (Circumferences are divided by 2):




1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Stretch factor horizontal 1.00 none (3/8 in)
6. Stretch factor vertical 1.00 none (3/8 in)
7. Front neck drop 8.65 cm (3 3/8 in)
8. Pocket entry length 11.95 cm (4 3/4 in)
9. Waist to pocket length 4.61 cm (1 7/8 in)
10. Side seam pocket position 2.86 cm (1 1/8 in)
11. Pocket width welt 3.00 cm (1 1/8 in)
12. Button diameter 1.00 cm (3/8 in)
13. Front buttons quantity 13.00 pc
14. Front length from HPS to hem 101.59 cm (40 in)
15. Across chest 50.38 cm (19 7/8 in)
16. Center front length to hem 93.14 cm (36 5/8 in)
17. Center back length to hem 98.38 cm (38 3/4 in)
18. Across front 36.61 cm (14 3/8 in)
19. Across back 35.11 cm (13 7/8 in)
20. Across shoulders 38.67 cm (15 1/4 in)






21. Side seam 73.83 cm (29 1/8 in)
22. Waist 42.96 cm (16 7/8 in)
23. Low hips 56.01 cm (22 in)
24. Hemline sweep 128.22 cm (50 1/2 in)
25. Armhole length front 23.35 cm (9 1/4 in)
26. Armhole length back 28.74 cm (11 3/8 in)
27. Neck opening 15.37 cm (6 in)
28. Back neck drop 3.65 cm (1 3/8 in)
29. Shoulder width 12.13 cm (4 3/4 in)
30. Neckline length 43.38 cm (17 1/8 in)
31. Seam allowance poc max 3.00 none (1 1/8 in)
32. Pocket bag height 16.92 cm (6 5/8 in)
33. Sleeve length 58.11 cm (22 7/8 in)
34. Sleeve upper arm width 33.65 cm (13 1/4 in)
35. Sleeve opening 24.79 cm (9 3/4 in)
36. Sleeve cap length 53.34 none (21 in)
37. Stand height 3.00 cm (1 1/8 in)
38. Collar length 43.38 cm (17 1/8 in)


Paper Size: A0;
Print Actual Size (100% Scale);











1



