CozySewPatterns
Free sewing patterns · cozysewpatterns.com

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 109.25, Waist: 93.25, Hips: 115.5
Pattern Name: -

Notes

How to print

Printing


Once your Calibration Test Page has been printed, measure the 4”x 4” (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.



Pattern Name: -
Seam Allowance: 1 (3/8 in)

Pattern pieces:


1. "FRONT", MAIN FABRIC: Cut 2
2. "BACK", MAIN FABRIC: Cut 2
3. "SLEEVE", MAIN FABRIC: Cut 2
4. "FRONT BOTTOM RUFFLE", MAIN FABRIC: Cut 1
5. "BACK BOTTOM RUFFLE", MAIN FABRIC: Cut 1
6. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
7. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
8. "COLLAR STAND", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2


Pattern Specs (Circumferences are divided by 2):


1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Stretch factor horizontal 1.00 none (3/8 in)
6. Stretch factor vertical 1.00 none (3/8 in)
7. Front neck drop 9.09 cm (3 5/8 in)
8. Button diameter 1.00 cm (3/8 in)
9. Front buttons quantity 8.00 pc
10. Across chest 57.51 cm (22 5/8 in)
11. Waist 50.41 cm (19 7/8 in)
12. Front length from HPS to hem 61.53 cm (24 1/4 in)
13. Center front length to hem 52.62 cm (20 3/4 in)
14. Center back length to hem 56.17 cm (22 1/8 in)
15. Across front 41.55 cm (16 3/8 in)
16. Across back 37.29 cm (14 5/8 in)
17. Across shoulders 42.31 cm (16 5/8 in)
18. Side seam 28.28 cm (11 1/8 in)
19. Hemline sweep 59.85 cm (23 5/8 in)
20. Armhole length front 25.55 cm (10 in)
21. Armhole length back 30.06 cm (11 7/8 in)
22. Neck opening 16.21 cm (6 3/8 in)
23. Neckline length 45.72 cm (18 in)


24. Back neck drop 3.73 cm (1 1/2 in)
25. Shoulder width 12.68 cm (5 in)
26. Bust dart to bust dart 26.90 cm (10 5/8 in)
27. Sleeve length 53.65 cm (21 1/8 in)
28. Sleeve upper arm width 40.74 cm (16 in)
29. Sleeve opening 26.01 cm (10 1/4 in)
30. Sleeve cap length 57.06 none (22 1/2 in)
31. Ruffle length 15.00 cm (5 7/8 in)
32. Stand height 3.00 cm (1 1/8 in)
33. Collar length 45.72 cm (18 in)

Paper Size: LETTER;
Print Actual Size (100% Scale);












4


FRONT BOTTOM RUFFLE


MAIN FABRIC: Cut 1


BACK NECK FACING
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2











6


FRONT NECK FACING


MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2








MAIN FABRIC: Cu
3/2



5
3/3
BACK BOTTOM RI



3/4









4/2


JEEI E


4/3









3
SLEEVE
MAIN FABRIC: Cut 2



ASE




















6/5











2
BACK
MAIN FABRIC: Cut 2

7/5


8
COLLAR STAND
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2
8/1

8/2




8/3

8/4

8/5