CozySewPatterns

SEWING PATTERNS

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 119.25, Waist: 104.75, Hips: 125.75
SIZE 20

Notes

How to print

Printing


Once your Calibration Test Page has been printed, measure the 4”x 4” (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.



SIZE 20
Seam Allowance: 1 (3/8 in)

Pattern pieces:

1. "PANTS FRONT", MAIN FABRIC: Cut 2
2. "PANTS BACK", MAIN FABRIC: Cut 2
3. "WAISTBAND LEFT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
4. "WAISTBAND RIGHT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
5. "POCKET BAG", MAIN FABRIC: Cut 2
6. "FLY FACING", MAIN FABRIC: Cut 1
7. "POCKET LINING", LINING: Cut 2
8. "FLY INTERFACING", FUSIBLE INTERFACING: Cut 1
9. "FUSIBLE INTERFACING FOR WAISTBAND", FUSIBLE INTERFACING: Cut 2
10. "BACK POCKET WELT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
11. "BACK INNER POCKET BAG", LINING: Cut 2
12. "BACK OUTER POCKET BAG", LINING: Cut 2

Pattern Specs (Circumferences are divided by 2):


1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Stretch factor 1.00 none (3/8 in)
4. Stretch factor horizontal 1.00 none (3/8 in)
5. Stretch factor vertical 1.00 none (3/8 in)
6. Pocket bag height 30.83 cm (12 1/8 in)
7. Pocket side seam 20.70 cm (8 1/8 in)
8. Pocket waist seam 20.70 cm (8 1/8 in)
9. Back pocket entry length 14.55 cm (5 3/4 in)
10. Side seam back pocket position 11.11 cm (4 3/8 in)
11. Waist to back pocket length 13.99 cm (5 1/2 in)
12. Back pocket width welt 2.50 cm (1 in)
13. Fly zipper length 23.00 cm (9 in)
14. Waist 55.88 cm (22 in)
15. Hips 65.78 cm (25 7/8 in)
16. Pleat depth 1.64 cm (5/8 in)
17. Thigh 41.92 cm (16 1/2 in)


18. Knee 33.53 cm (13 1/4 in)
19. Bottom opening 23.16 cm (9 1/8 in)
20. Front rise 33.71 cm (13 1/4 in)
21. Back rise 49.44 cm (19 1/2 in)
22. Crotch height 31.87 cm (12 1/2 in)
23. Inseam length 65.66 cm (25 7/8 in)
24. Pants side seam length 99.09 cm (39 in)
25. Waistband partly elastic width 3.00 cm (1 1/8 in)
26. Waistband width 3.30 cm (1 1/4 in)
27. Waistband length 120.89 cm (47 5/8 in)
28. Waistband partly elastic length 59.11 cm (23 1/4 in)
29. Waistband button diameter 1.00 cm (3/8 in)
30. Waistband buttons quantity 1.00 pc
31. Seam allowance poc max 3.00 none (1 1/8 in)
32. Back pocket bag height 12.37 cm (4 7/8 in)


CozySewPatterns

SEWING PATTERNS

Paper Size: A4;
Print Actual Size (100% Scale);





12
BACK OUTER POCKET BAG
LINING: Cut 2
10
BACK POCKET WELT
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2
9
FUSIBLE INTERFACING FOR WAISTBA
1/1




2

PANTS BAC

MAIN FABRIC: C







1

PANTS FRONT

MAIN FABRIC: Cut 2



6
FLY FACING
MAIN FABRIC: Cut 1



5
POCKET BAG
MAIN FABRIC: Cut 2
1/9


7


POCKET LINING

LINING: Cut 2




2/1





8

FLY INTERFACING

FUSIBLE INTERFACING: Cut 1

11

BACK INNER POCKET BAG

LINING: Cut 2


NTER FRONT


3

WAISTBAND LE


MAIN FABRIC: Cut


FUSIBLE INTERFACING



WAISTLINE
ELASTIC
FOLD




3/2


CLIENT





3/7






FEET FRONT L


ELASTIC LENGTH 23 1/4" (59.11

SIDE SEAM

4


WAISTBAND RIGHT
MAIN FABRIC: Cut 1
FUSIBLE INTERFACING: Cut 1



) cm
CENTER BACK




FOLD




SIDE SEAM


ELASTIC


CENTER
FRONT