CozySewPatterns

SEWING PATTERNS

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 114.25, Waist: 99, Hips: 120.75
SIZE 18

Notes

How to print

Printing


Once your Calibration Test Page has been printed, measure the 4”x 4” (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.



SIZE 18
Seam Allowance: 1 (3/8 in)

Pattern pieces:

1. "PANTS FRONT", MAIN FABRIC: Cut 2
2. "PANTS BACK", MAIN FABRIC: Cut 2
3. "WAISTBAND", MAIN FABRIC: Cut 1
4. "POCKET BAG", MAIN FABRIC: Cut 2
5. "FLY FACING", MAIN FABRIC: Cut 1
6. "POCKET LINING", LINING: Cut 2
7. "FLY INTERFACING", FUSIBLE INTERFACING: Cut 1
8. "FUSIBLE INTERFACING FOR WAISTBAND", FUSIBLE INTERFACING: Cut 2
9. "BACK POCKET WELT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
10. "BACK INNER POCKET BAG", LINING: Cut 2
11. "BACK OUTER POCKET BAG", LINING: Cut 2

Pattern Specs (Circumferences are divided by 2):


1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Stretch factor 1.00 none (3/8 in)
4. Stretch factor horizontal 1.00 none (3/8 in)
5. Stretch factor vertical 1.00 none (3/8 in)
6. Pocket bag height 30.26 cm (11 7/8 in)
7. Pocket side seam 20.27 cm (8 in)
8. Pocket waist seam 20.27 cm (8 in)
9. Back pocket entry length 14.36 cm (5 5/8 in)
10. Side seam back pocket position 10.46 cm (4 1/8 in)
11. Waist to back pocket length 13.79 cm (5 3/8 in)
12. Back pocket width welt 2.50 cm (1 in)
13. Fly zipper length 23.00 cm (9 in)
14. Waist 53.14 cm (20 7/8 in)
15. Hips 62.89 cm (24 3/4 in)
16. Pleat depth 1.57 cm (5/8 in)
17. Thigh 40.11 cm (15 3/4 in)
18. Knee 32.15 cm (12 5/8 in)
19. Bottom opening 22.37 cm (8 3/4 in)

20. Front rise 33.00 cm (13 in)
21. Back rise 47.95 cm (18 7/8 in)
22. Crotch height 31.21 cm (12 1/4 in)
23. Inseam length 66.39 cm (26 1/8 in)
24. Pants side seam length 98.96 cm (39 in)
25. Waistband partly elastic width 3.00 cm (1 1/8 in)
26. Waistband width 3.30 cm (1 1/4 in)
27. Waistband length 115.47 cm (45 1/2 in)
28. Waistband partly elastic length 56.18 cm (22 1/8 in)
29. Waistband button diameter 1.00 cm (3/8 in)
30. Waistband buttons quantity 1.00 pc
31. Seam allowance poc max 3.00 none (1 1/8 in)
32. Back pocket bag height 12.20 cm (4 3/4 in)


CozySewPatterns

SEWING PATTERNS


Paper Size: LETTER;
Print Actual Size (100% Scale);



MAIN FABRIC




1/1




2

PANTS BA



PANTS FRONT

MAIN FABRIC: Cut 2





4
POCKET BAG
MAIN FABRIC: Cut 2


6

POCKET LINING

LINING: Cut 2





: Cut 2





2/1


ACK 2/2








11
BACK OUTER POCKET BAG
LINING: Cut 2



9
BACK POCKET WELT
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2



3/2









10


BACK INNER POCKET BAG


LINING: Cut 2


3/6








CUT ON LEFT FRONT






CENTER FRONT
WAISTBAND
MAIN FABRIC: Cut 1
3


5/2





5/3

1/8" (56.18) cm

5/4




SIDE SEAM


ELASTIC
CENTER
FRONT