
cozysewpatterns

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 82.5, Waist: 66, Hips: 90.25
SIZE 0

Notes



How to print

Printing

Once your Calibration Test Page has been printed, measure the 4”x 4” (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.

cozysewpatterns

SIZE 0
Seam Allowance: 1 (3/8 in)

Pattern pieces:

1. "PANTS FRONT", MAIN FABRIC: Cut 2
2. "PANTS BACK", MAIN FABRIC: Cut 2
3. "WAISTBAND", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
4. "POCKET BAG", MAIN FABRIC: Cut 2
5. "FLY FACING", MAIN FABRIC: Cut 1
6. "POCKET LINING", LINING: Cut 2
7. "FLY INTERFACING", FUSIBLE INTERFACING: Cut 1
8. "BACK POCKET WELT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
9. "BACK INNER POCKET BAG", LINING: Cut 2
10. "BACK OUTER POCKET BAG", LINING: Cut 2


Pattern Specs (Circumferences are divided by 2):


1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Stretch factor 1.00 none (3/8 in)
4. Stretch factor horizontal 1.00 none (3/8 in)
5. Stretch factor vertical 1.00 none (3/8 in)
6. Pocket bag height 26.90 cm (10 5/8 in)
7. Pocket side seam 17.73 cm (7 in)
8. Pocket waist seam 17.73 cm (7 in)
9. Back pocket entry length 12.00 cm (4 3/4 in)
10. Side seam back pocket position 5.14 cm (2 in)
11. Waist to back pocket length 10.09 cm (4 in)
12. Back pocket width welt 2.50 cm (1 in)
13. Fly zipper length 23.00 cm (9 in)
14. Waist 33.66 cm (13 1/4 in)
15. Hips 45.54 cm (17 7/8 in)
16. Pleat depth 1.13 cm (1/2 in)
17. Thigh 29.12 cm (11 1/2 in)
18. Knee 23.72 cm (9 3/8 in)
19. Bottom opening 17.24 cm (6 3/4 in)
20. Front rise 28.73 cm (11 1/4 in)
21. Back rise 37.72 cm (14 7/8 in)


22. Crotch height 27.29 cm (10 3/4 in)
23. Inseam length 70.29 cm (27 5/8 in)
24. Pants side seam length 98.14 cm (38 5/8 in)
25. Waistband width 3.00 cm (1 1/8 in)
26. Waistband length 70.31 cm (27 5/8 in)
27. Waistband button diameter 1.00 cm (3/8 in)
28. Waistband buttons quantity 1.00 pc
29. Seam allowance poc max 3.00 none (1 1/8 in)
30. Back pocket bag height 10.20 cm (4 in)


cozysewpatterns

Paper Size: A4;
Print Actual Size (100% Scale);







5
FLY FACING
MAIN FABRIC: Cut 1
1/1



2

PANTS BACK


MAIN FABRIC: Cut 2



6

POCKET LINING

LINING: Cut 2




7


FLY INTERFACING


FUSIBLE INTERFACING: Cut 1


POCKET BAG

MAIN FABRIC: Cut 2




4





10

BACK OUTER POCKET BAG

LINING: Cut 2

9

BACK INNER POCKET BAG


LINING: Cut 2


8

BACK POCKET WELT


MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2






3/2




P
MA




4/3


1

ANTS FRONT

AIN FABRIC: Cut 2




5/1



CUT ON LEFT FRONT

5/3

5/4




6/2




6/3

6/4

6/5





7/3


7/4

7/5


8/1

CENTER FRONT
3
WAISTBAND
MAIN FABRIC: Cut 1
FUSIBLE INTERFACING: Cut 1


8/2



8/3



8/4



8/5