cozysewpatterns

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 95.25, Waist: 78.75, Hips: 102.75
SIZE 10

Notes

How to print

Printing


Once your Calibration Test Page has been printed, measure the 4”x 4” (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.



SIZE 10
Seam Allowance: 1 (3/8 in)

Pattern pieces:

1. "RIGHT CENTER FRONT", MAIN FABRIC: Cut 1
2. "LEFT CENTER FRONT", MAIN FABRIC: Cut 1
3. "SIDE FRONT", MAIN FABRIC: Cut 2
4. "CENTER BACK", MAIN FABRIC: Cut 2
5. "SIDE BACK", MAIN FABRIC: Cut 2
6. "LEFT FRONT BUTTON FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
7. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
8. "FRONT ARMHOLE FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
9. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
10. "BACK ARMHOLE FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
11. "RIGHT FRONT PLACKET", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1


Pattern Specs (Circumferences are divided by 2):

1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Stretch factor horizontal 1.00 none (3/8 in)
6. Stretch factor vertical 1.00 none (3/8 in)
7. Front neck drop 17.31 cm (6 7/8 in)
8. Back invisible zipper length 18.00 cm (7 1/8 in)
9. Button diameter 1.00 cm (3/8 in)
10. Front buttons quantity 12.00 pc
11. Front length from HPS to hem 101.92 cm (40 1/8 in)
12. Across chest 50.38 cm (19 7/8 in)
13. Center front length to hem 87.19 cm (34 3/8 in)
14. Center back length to hem 98.88 cm (38 7/8 in)
15. Across front 35.22 cm (13 7/8 in)
16. Across back 35.11 cm (13 7/8 in)


17. Across shoulders 38.68 cm (15 1/4 in)
18. Side seam 75.91 cm (29 7/8 in)
19. Waist 42.96 cm (16 7/8 in)
20. Low hips 56.01 cm (22 in)
21. Hemline sweep 72.07 cm (28 3/8 in)
22. Armhole length front 22.03 cm (8 5/8 in)
23. Armhole length back 25.90 cm (10 1/4 in)
24. Neck opening 19.95 cm (7 7/8 in)
25. Back neck drop 5.65 cm (2 1/4 in)
26. Shoulder width 9.70 cm (3 7/8 in)
27. Neckline length 61.96 cm (24 3/8 in)
28. Placket length 87.19 cm (34 3/8 in)
29. Placket width 3.00 cm (1 1/8 in)


cozysewpatterns


Paper Size: A4;
Print Actual Size (100% Scale);





8
FRONT ARMHOLE FACING
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2



2
LEFT CENTER FRONT
MAIN FABRIC: Cut 1
9
BACK NECK FACING
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2
1/2















3/2






5
SIDE BACK
MAIN FABRIC: Cut 2
4/1


4/2
CK
ut 2



5/1






4


CENTER BA


MAIN FABRIC: C

6/1



6/2







3


SIDE FRONT

MAIN FABRIC: Cut 2






ZIP



8/2




11

RIGHT FRONT PLACKET

MAIN FABRIC: Cut 1

FUSIBLE INTERFACING: Cut 1




6

LEFT FRONT BUTTON FACING

MAIN FABRIC: Cut 1


FUSIBLE INTERFACING: Cut 1





1

RIGHT CENTER FRONT


MAIN FABRIC: Cut 1










FOLD


11/2
7
FRONT NECK FACING
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2







BACK ARMHOLE FACING

MAIN FABRIC: Cut 2

FUSIBLE INTERFACING: Cut 2

12/3

13/1

13/2

13/3

14/1

14/2

14/3

15/1

15/2

I

15/3