cozysewpatterns

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 104.25, Waist: 87.5, Hips: 111
SIZE 14

Notes

How to print

Printing


Once your Calibration Test Page has been printed, measure the 4”x 4” (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.



SIZE 14
Seam Allowance: 1 (3/8 in)

Pattern pieces:

1. "RIGHT CENTER FRONT", MAIN FABRIC: Cut 1
2. "LEFT CENTER FRONT", MAIN FABRIC: Cut 1
3. "SIDE FRONT", MAIN FABRIC: Cut 2
4. "CENTER BACK", MAIN FABRIC: Cut 2
5. "SIDE BACK", MAIN FABRIC: Cut 2
6. "LEFT FRONT BUTTON FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
7. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
8. "FRONT ARMHOLE FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
9. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
10. "BACK ARMHOLE FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
11. "RIGHT FRONT PLACKET", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1


Pattern Specs (Circumferences are divided by 2):


1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Stretch factor horizontal 1.00 none (3/8 in)
6. Stretch factor vertical 1.00 none (3/8 in)
7. Front neck drop 18.17 cm (7 1/8 in)
8. Back invisible zipper length 18.00 cm (7 1/8 in)
9. Button diameter 1.00 cm (3/8 in)
10. Front buttons quantity 12.00 pc
11. Front length from HPS to hem 103.68 cm (40 7/8 in)
12. Across chest 54.96 cm (21 5/8 in)
13. Center front length to hem 88.12 cm (34 3/4 in)
14. Center back length to hem 99.46 cm (39 1/8 in)
15. Across front 38.67 cm (15 1/4 in)
16. Across back 36.56 cm (14 3/8 in)

17. Across shoulders 40.23 cm (15 7/8 in)
18. Side seam 75.79 cm (29 7/8 in)
19. Waist 47.43 cm (18 5/8 in)
20. Low hips 60.44 cm (23 3/4 in)
21. Hemline sweep 76.50 cm (30 1/8 in)
22. Armhole length front 23.22 cm (9 1/8 in)
23. Armhole length back 27.05 cm (10 5/8 in)
24. Neck opening 20.73 cm (8 1/8 in)
25. Back neck drop 5.80 cm (2 1/4 in)
26. Shoulder width 10.08 cm (4 in)
27. Neckline length 64.69 cm (25 1/2 in)
28. Placket length 88.12 cm (34 3/4 in)
29. Placket width 3.00 cm (1 1/8 in)

cozysewpatterns

Paper Size: A4;
Print Actual Size (100% Scale);




8
FRONT ARMHOLE FACING
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2

1/2

7

FRONT NECK FACING

MAIN FABRIC: Cut 2

FUSIBLE INTERFACING: Cut 2


2


LEFT CENTER FRONT


MAIN FABRIC: Cut 1

1/3

2/1









3


SIDE FRONT


MAIN FABRIC: Cut 2





3/2













5


SIDE BACK


MAIN FABRIC: Cut 2


5/2

















7/1



4
CENTER BACK
MAIN FABRIC: Cut 2
12









10
BACK ARMHOLE FACING
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2
6
LEFT FRONT BUTTON FACING
MAIN FABRIC: Cut 1
FUSIBLE INTERFACING: Cut 1
11
RIGHT FRONT PLACKET
MAIN FABRIC: Cut 1
FUSIBLE INTERFACING: Cut 1
8/2


8/3













10/2

10/3

FOLD

RIGHT CENTER FRONT

MAIN FABRIC: Cut 1

11/2


9


BACK NECK FA

MAIN FABRIC: C

FUSIBLE INTERFACIN

11/3




CING
ut 2
IG: Cut 2

12/3