
cozysewpatterns

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 82.5, Waist: 66, Hips: 90.25
SIZE 0

Notes



How to print

Printing

Once your Calibration Test Page has been printed, measure the 4”x 4” (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.

SIZE 0
Seam Allowance: 1 (3/8 in)

Pattern pieces:

1. "FRONT LINING", LINING: Cut 2
2. "CENTER FRONT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
3. "SIDE FRONT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
4. "CENTER BACK", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
5. "CENTER BACK LINING", LINING: Cut 1
6. "SIDE BACK", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
7. "SIDE BACK LINING", LINING: Cut 2
8. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
9. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
10. "UPPER COLLAR", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
11. "LOWER COLLAR", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
12. "BELT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
13. "PATCH POCKET", MAIN FABRIC: Cut 2
14. "TWO BELT LOOPS", MAIN FABRIC: Cut 1
15. "UPPER SLEEVE", MAIN FABRIC: Cut 2
16. "LOWER SLEEVE", MAIN FABRIC: Cut 2
17. "UPPER SLEEVE LINING", LINING: Cut 2
18. "LOWER SLEEVE LINING", LINING: Cut 2


Pattern Specs (Circumferences are divided by 2):


1. Hem max 4.60 none (1 3/4 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Shoulder pads thickness 1.00 none (3/8 in)
6. Pocket entry length 11.16 cm (4 3/8 in)
7. Waist to pocket length 9.79 cm (3 7/8 in)
8. Side seam pocket position 2.64 cm (1 in)
9. Button diameter 1.50 cm (5/8 in)
10. Front buttons quantity 12.00 pc
11. Front length from HPS to hem 88.41 cm (34 3/4 in)
12. Across chest 47.27 cm (18 5/8 in)
13. Center front length to hem 79.17 cm (31 1/8 in)

14. Center back length to hem 87.13 cm (34 1/4 in)
15. Across front 31.24 cm (12 1/4 in)
16. Across back 37.60 cm (14 3/4 in)
17. Across shoulders 38.26 cm (15 1/8 in)
18. Side seam 64.99 cm (25 5/8 in)
19. Waist 40.00 cm (15 3/4 in)
20. Low hips 50.62 cm (19 7/8 in)
21. Blazer hemline sweep 55.57 cm (21 7/8 in)
22. Armhole length 47.28 cm (18 5/8 in)
23. Neck opening 17.40 cm (6 7/8 in)
24. Front neck drop 17.83 cm (7 in)
25. Back neck drop 3.75 cm (1 1/2 in)
26. Shoulder width 12.16 cm (4 3/4 in)
27. Apex to apex 17.50 cm (6 7/8 in)
28. Seam allowance poc max 3.00 none (1 1/8 in)
29. Hem poc max 6.00 none (2 3/8 in)
30. Pocket height 12.27 cm (4 7/8 in)
31. Stretch factor horizontal 1.00 none (3/8 in)
32. Stretch factor vertical 1.00 none (3/8 in)
33. Sleeve length 58.59 none (23 1/8 in)
34. Sleeve cap length 48.62 none (19 1/8 in)
35. Armhole length 47.28 none (18 5/8 in)
36. Sleeve upper arm width 30.54 none (12 in)
37. Sleeve opening 22.66 none (8 7/8 in)

cozysewpatterns

Paper Size: A4;
Print Actual Size (100% Scale);






5

CENTER BACK LINING

LINING: Cut 1





2


CENTER FRONT


MAIN FABRIC: Cut 2

FUSIBLE INTERFACING: Cut 2









14
TWO BELT LOOPS
MAIN FABRIC: Cut 1



12
BELT
MAIN FABRIC: Cut 1
FUSIBLE INTERFACING: Cut 1


2/1


















3/2






3/4





















8

FRONT NECK FACING


MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2


5/2




5/4







CEN
MAIN F
FUSIBLE IN
6/1




1


FRONT LIN

LINING: Cu



6/3






4

TER BACK

FABRIC: Cut 2


TERFACING: Cut 2





15

UPPER SLEEVE

MAIN FABRIC: Cut 2




ING
t 2
7/3




17

UPPER SLEEVE L


LINING: Cut 2

7/4


7/5


8/1

8/2



8/3



8/4 GNINI


8/5

10


UPPER COLLAR


MAIN FABRIC: Cut 1

FUSIBLE INTERFACING:



18
LOWER SLEEVE LINING
LINING: Cut 2
9/1


EASE


1
LOWER S
MAIN FABR


9/4

Cut 1





10/1

3


SIDE FRONT

MAIN FABRIC: Cut 2

FUSIBLE INTERFACING: Cut 2



10/2





6


LEEVE

C: Cut 2

10/3








7


SIDE BACK

LINING:

11/1

11/2





11

LOWER COLLAR

MAIN FABRIC: Cut 1


FUSIBLE INTERFACING: Cut 1

6


SIDE BACK


MAIN FABRIC: Cut 2

FUSIBLE INTERFACING: Cut 2



1 1/4








K LINING

Cut 2

121







13
12/4
PATCH POCKET
MAIN FABRIC: Cut 2

12/5

13/1

13/2



13/4

13/5