
cozysewpatterns

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 87.75, Waist: 71.25, Hips: 95.25
SIZE 4

Notes



How to print

Printing

Once your Calibration Test Page has been printed, measure the 4”x 4” (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.

SIZE 4
Seam Allowance: 1 (3/8 in)

Pattern pieces:

1. "FRONT LINING", LINING: Cut 2
2. "CENTER FRONT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
3. "SIDE FRONT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
4. "CENTER BACK", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
5. "CENTER BACK LINING", LINING: Cut 1
6. "SIDE BACK", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
7. "SIDE BACK LINING", LINING: Cut 2
8. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
9. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
10. "UPPER COLLAR", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
11. "LOWER COLLAR", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
12. "BELT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
13. "PATCH POCKET", MAIN FABRIC: Cut 2
14. "TWO BELT LOOPS", MAIN FABRIC: Cut 1
15. "UPPER SLEEVE", MAIN FABRIC: Cut 2
16. "LOWER SLEEVE", MAIN FABRIC: Cut 2
17. "UPPER SLEEVE LINING", LINING: Cut 2
18. "LOWER SLEEVE LINING", LINING: Cut 2


Pattern Specs (Circumferences are divided by 2):


1. Hem max 4.60 none (1 3/4 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Shoulder pads thickness 1.00 none (3/8 in)
6. Pocket entry length 11.48 cm (4 1/2 in)
7. Waist to pocket length 9.86 cm (3 7/8 in)
8. Side seam pocket position 3.63 cm (1 3/8 in)
9. Button diameter 1.50 cm (5/8 in)
10. Front buttons quantity 12.00 pc
11. Front length from HPS to hem 89.32 cm (35 1/8 in)
12. Across chest 50.01 cm (19 3/4 in)
13. Center front length to hem 79.90 cm (31 1/2 in)

14. Center back length to hem 87.62 cm (34 1/2 in)
15. Across front 33.69 cm (13 1/4 in)
16. Across back 38.68 cm (15 1/4 in)
17. Across shoulders 39.19 cm (15 3/8 in)
18. Side seam 63.75 cm (25 1/8 in)
19. Waist 42.62 cm (16 3/4 in)
20. Low hips 53.71 cm (21 1/8 in)
21. Blazer hemline sweep 58.66 cm (23 1/8 in)
22. Armhole length 51.16 cm (20 1/8 in)
23. Neck opening 17.68 cm (7 in)
24. Front neck drop 18.14 cm (7 1/8 in)
25. Back neck drop 3.78 cm (1 1/2 in)
26. Shoulder width 12.47 cm (4 7/8 in)
27. Apex to apex 18.55 cm (7 1/4 in)
28. Seam allowance poc max 3.00 none (1 1/8 in)
29. Hem poc max 6.00 none (2 3/8 in)
30. Pocket height 12.63 cm (5 in)
31. Stretch factor horizontal 1.00 none (3/8 in)
32. Stretch factor vertical 1.00 none (3/8 in)
33. Sleeve length 58.70 none (23 1/8 in)
34. Sleeve cap length 52.57 none (20 3/4 in)
35. Armhole length 51.16 none (20 1/8 in)
36. Sleeve upper arm width 32.15 none (12 5/8 in)
37. Sleeve opening 24.68 none (9 3/4 in)

cozysewpatterns

Paper Size: A4;
Print Actual Size (100% Scale);






5

CENTER BACK LINING

LINING: Cut 1





2

CENTER FRONT

MAIN FABRIC: Cut 2

FUSIBLE INTERFACING: Cut 2







12


BELT


MAIN FABRIC: Cut 1


FUSIBLE INTERFACING: Cut 1















3/2























14
TWO BELT LOOPS
MAIN FABRIC: Cut 1












5/4





CE
MA
FUSIBLE




1


FRONT L

LINING:



6/3






4

ENTER BACK

IN FABRIC: Cut 2

E INTERFACING: Cut 2



11

LOWER COLLAR

MAIN FABRIC: Cut 1

FUSIBLE INTERFACING: Cut 1

FRONT NECK FACING


MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2


15

ER SLEEVE

FABRIC: Cut 2


.IINING
Cut 2
7/3
8


EASE
17
UPPER SLEEV
LINING: C




8/2

UPP

MAIN

8/3





7


'E LINING


ut 2


8/4






EASE


LO
MA




6


SIDE BACK


MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2

9/4










16


WER SLEEVE

IN FABRIC: Cut 2

10/3


10/4






3

SIDE FRONT


MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2


L1/1




11/2




PATCH
MAIN FA
UP
MA
FUSIBLE
11/4






7

ACK LINING

NG: Cut 2





12/2


18

LOWER SLEEVE LINING

LINING: Cut 2






POCKET
BRIC: Cut 2
10
PER COLLAR
IN FABRIC: Cut 1
E INTERFACING: Cut 1
12/4



13/1

13/2





13/5