
cozysewpatterns

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 124.25, Waist: 110.5, Hips: 130.75
SIZE 22

Notes



How to print

Printing

Once your Calibration Test Page has been printed, measure the 4”x 4” (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.

SIZE 22
Seam Allowance: 1 (3/8 in)

Pattern pieces:

1. "FRONT LINING", LINING: Cut 2
2. "CENTER FRONT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
3. "SIDE FRONT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
4. "CENTER BACK", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
5. "CENTER BACK LINING", LINING: Cut 1
6. "SIDE BACK", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
7. "SIDE BACK LINING", LINING: Cut 2
8. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
9. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
10. "UPPER COLLAR", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
11. "LOWER COLLAR", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
12. "BELT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
13. "PATCH POCKET", MAIN FABRIC: Cut 2
14. "TWO BELT LOOPS", MAIN FABRIC: Cut 1
15. "UPPER SLEEVE", MAIN FABRIC: Cut 2
16. "LOWER SLEEVE", MAIN FABRIC: Cut 2
17. "UPPER SLEEVE LINING", LINING: Cut 2
18. "LOWER SLEEVE LINING", LINING: Cut 2


Pattern Specs (Circumferences are divided by 2):


1. Hem max 4.60 none (1 3/4 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Shoulder pads thickness 1.00 none (3/8 in)
6. Pocket entry length 13.77 cm (5 3/8 in)
7. Waist to pocket length 10.27 cm (4 in)
8. Side seam pocket position 11.77 cm (4 5/8 in)
9. Button diameter 1.50 cm (5/8 in)
10. Front buttons quantity 12.00 pc
11. Front length from HPS to hem 95.74 cm (37 3/4 in)
12. Across chest 70.79 cm (27 7/8 in)
13. Center front length to hem 85.09 cm (33 1/2 in)

14. Center back length to hem 89.34 cm (35 1/8 in)
15. Across front 49.64 cm (19 1/2 in)
16. Across back 45.49 cm (17 7/8 in)
17. Across shoulders 44.14 cm (17 3/8 in)
18. Side seam 61.04 cm (24 in)
19. Waist 63.07 cm (24 7/8 in)
20. Low hips 74.55 cm (29 3/8 in)
21. Blazer hemline sweep 79.48 cm (31 1/4 in)
22. Armhole length 66.23 cm (26 1/8 in)
23. Neck opening 20.04 cm (7 7/8 in)
24. Front neck drop 21.64 cm (8 1/2 in)
25. Back neck drop 3.89 cm (1 1/2 in)
26. Shoulder width 13.78 cm (5 3/8 in)
27. Apex to apex 25.85 cm (10 1/8 in)
28. Seam allowance poc max 3.00 none (1 1/8 in)
29. Hem poc max 6.00 none (2 3/8 in)
30. Pocket height 15.14 cm (6 in)
31. Stretch factor horizontal 1.00 none (3/8 in)
32. Stretch factor vertical 1.00 none (3/8 in)
33. Sleeve length 59.56 none (23 1/2 in)
34. Sleeve cap length 68.34 none (26 7/8 in)
35. Armhole length 66.23 none (26 1/8 in)
36. Sleeve upper arm width 47.11 none (18 1/2 in)
37. Sleeve opening 29.01 none (11 3/8 in)

cozysewpatterns

Paper Size: A4;
Print Actual Size (100% Scale);








5

CENTER BACK LINING

LINING: Cut 1








2

CENTER FRONT


MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2



14
TWO BELT LOOPS
MAIN FABRIC: Cut 1

2/1












3/1





3/2














1


FRONT LINING

LINING: Cut 2



MAIN FABRIC: Cut 1
FUSIBLE INTERFACING: Cut 1
4/2


C
M
FUSIBL
4/3
12
BELT






5/1



5/2




4

CENTER BACK

AIN FABRIC: Cut 2


LE INTERFACING: Cut 2





18


LOWER SLEEVE LINING


LINING: Cut 2













11


LOWER COLLAR


MAIN FABRIC: Cut 1


FUSIBLE INTERFACING: Cut 1


























UPPER SLEEVE LININ
LINING: Cut 2
8/3




17








9/2


NG




9/3








8
FRONT NECK FACING
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2



UPPER S
MAIN FABR


EASE



10
UPPER COLLAR
MAIN FABRIC: Cut 1
FUSIBLE INTERFACING: Cut 1


3

SIDE FRONT

MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2







SLEEVE


RIC: Cut 2





11/3









12/1







12/4
7
E BACK LINING
LINING: Cut 2




13/1




6

SIDE BACK


MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2





13/4


SIDI





13
PATCH POCKET
MAIN FABRIC: Cut 2
14/1



16
LOWER SLEEVE
MAIN FABRIC: Cut 2
14/2









15/1


9
BACK NECK FACING
MAIN FABRIC: Cut 1
FUSIBLE INTERFACING: Cut 1





15/4

