cozysewpatterns

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 92.75, Waist: 76.25, Hips: 100.25
8

Notes

How to print

Printing


Once your Calibration Test Page has been printed, measure the 4”x 4” (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.



8
Seam Allowance: 1 (3/8 in)

Pattern pieces:

1. "FRONT", MAIN FABRIC: Cut 2
2. "BACK", MAIN FABRIC: Cut 1
3. "SLEEVE", MAIN FABRIC: Cut 2
4. "CUFF", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
5. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
6. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
7. "COLLAR", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
8. "EDGING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2


Pattern Specs (Circumferences are divided by 2):


1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Stretch factor horizontal 1.00 none (3/8 in)
6. Stretch factor vertical 1.00 none (3/8 in)
7. Front neck drop 14.71 cm (5 3/4 in)
8. Front length from HPS to hem 68.22 cm (26 7/8 in)
9. Across chest 49.12 cm (19 3/8 in)
10. Center front length to hem 53.51 cm (21 1/8 in)
11. Center back length to hem 64.22 cm (25 1/4 in)
12. Across front 35.47 cm (14 in)
13. Across back 35.11 cm (13 7/8 in)
14. Across shoulders 40.00 cm (15 3/4 in)
15. Side seam 34.28 cm (13 1/2 in)
16. Waist 41.68 cm (16 3/8 in)
17. Hips 54.47 cm (21 1/2 in)
18. Hemline sweep 70.27 cm (27 5/8 in)
19. Armhole length front 22.98 cm (9 in)
20. Armhole length back 26.98 cm (10 5/8 in)
21. Neck opening 20.41 cm (8 in)
22. Neckline length 61.00 cm (24 in)
23. Back neck drop 3.45 cm (1 3/8 in)


24. Shoulder width 9.43 cm (3 3/4 in)
25. Bust dart to bust dart 23.13 cm (9 1/8 in)
26. Sleeve length 55.40 cm (21 3/4 in)
27. Sleeve upper arm width 32.50 cm (12 3/4 in)
28. Cuff width 4.00 cm (1 5/8 in)
29. Cuff length 23.68 cm (9 3/8 in)
30. Sleeve cap length 51.09 none (20 1/8 in)
31. Cuff button diameter 0.50 cm (1/4 in)
32. Cuff buttons quantity 2.00 pc
33. Front exposed 7mm zipper length 53.53 cm (21 1/8 in)
34. Collar width 9.50 cm (3 3/4 in)
35. Collar edges length 9.00 cm (3 1/2 in)

cozysewpatterns

Paper Size: LETTER;
Print Actual Size (100% Scale);




8
EDGING





2


BACK


MAIN FABRIC: Cut 1


1/2




















3/2







MAIN FABRIC: Cut 2

FUSIBLE INTERFACING: Cut 2





3/5
5
FRONT NECK FACING



1


FRONT

MAIN FABRIC: Cut 2





SLEEVE


MAIN FABRIC: Cut 2




3









5/1





5/3






ZIP


FOLD
7
COLLAR
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2
6/2





6


BACK NECK FACING

MAIN FABRIC: Cut 1


FUSIBLE INTERFACING: Cut 1








6/5


FOLD
4
CUFF
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2
1/1


7/2
1

7/3

7/5