
cozysewpatterns

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 85, Waist: 68.75, Hips: 92.75
SIZE 2

Notes



How to print

Printing

Once your Calibration Test Page has been printed, measure the 4”x 4” (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.

SIZE 2
Seam Allowance: 1 (3/8 in)

Pattern pieces:

1. "CENTER FRONT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
2. "SIDE FRONT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
3. "CENTER BACK", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
4. "SIDE BACK", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
5. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
6. "FRONT ARMHOLE FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
7. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
8. "BACK ARMHOLE FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
9. "PATCH POCKET", MAIN FABRIC: Cut 2


Pattern Specs (Circumferences are divided by 2):


1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Shoulder pads thickness 1.00 none (3/8 in)
6. Pocket entry length 10.18 cm (4 in)
7. Waist to pocket length 2.51 cm (1 in)
8. Side seam pocket position 2.78 cm (1 1/8 in)
9. Button diameter 1.50 cm (5/8 in)
10. Front buttons quantity 6.00 pc
11. Front length from HPS to hem 58.68 cm (23 1/8 in)
12. Across chest 48.69 cm (19 1/8 in)
13. Center front length to hem 42.39 cm (16 3/4 in)
14. Center back length to hem 58.00 cm (22 7/8 in)
15. Across front 32.20 cm (12 5/8 in)
16. Across back 38.17 cm (15 in)
17. Across shoulders 38.77 cm (15 1/4 in)
18. Side seam 36.43 cm (14 3/8 in)
19. Waist 41.38 cm (16 1/4 in)
20. Low hips 52.10 cm (20 1/2 in)

21. Blazer hemline sweep 50.87 cm (20 in)
22. Armhole length 46.54 cm (18 3/8 in)
23. Neck opening 19.87 cm (7 7/8 in)
24. Front neck drop 14.14 cm (5 5/8 in)
25. Back neck drop 4.04 cm (1 5/8 in)
26. Shoulder width 12.30 cm (4 7/8 in)
27. Apex to apex 18.00 cm (7 1/8 in)
28. Seam allowance poc max 3.00 none (1 1/8 in)
29. Hem poc max 6.00 none (2 3/8 in)
30. Pocket height 11.20 cm (4 3/8 in)

cozysewpatterns

Paper Size: A4;
Print Actual Size (100% Scale);






1
CENTER FRONT
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2

CENTER BACK


MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2






3


2/1












5


FRONT NECK


MAIN FABRIC


FUSIBLE INTERFA

3/1


3/2
8
BACK ARMHOLE FACING
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2










K FACING


C: Cut 2

ACING: Cut 2


FRONT ARMHOLE FACING
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2
4
SIDE BACK
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2
4/2


9
4/3






2

SIDE FRONT


MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2

5/2



5/3
9
PATCH POCKET
MAIN FABRIC: Cut 2


6/1





6/3


7
BACK NECK FACING
MAIN FABRIC: Cut 1
FUSIBLE INTERFACING: Cut 1
T/2



7/3