cozysewpatterns

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 99.25, Waist: 82.75, Hips: 106.5
SIZE 12

Notes

How to print

Printing


Once your Calibration Test Page has been printed, measure the 4”x 4” (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.



SIZE 12
Seam Allowance: 1 (3/8 in)

Pattern pieces:

1. "CENTER FRONT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
2. "SIDE FRONT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
3. "CENTER BACK", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
4. "SIDE BACK", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
5. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
6. "FRONT ARMHOLE FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
7. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
8. "BACK ARMHOLE FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
9. "PATCH POCKET", MAIN FABRIC: Cut 2


Pattern Specs (Circumferences are divided by 2):


1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Shoulder pads thickness 1.00 none (3/8 in)
6. Pocket entry length 10.98 cm (4 3/8 in)
7. Waist to pocket length 2.47 cm (1 in)
8. Side seam pocket position 5.64 cm (2 1/4 in)
9. Button diameter 1.50 cm (5/8 in)
10. Front buttons quantity 6.00 pc
11. Front length from HPS to hem 60.77 cm (23 7/8 in)
12. Across chest 56.18 cm (22 1/8 in)
13. Center front length to hem 43.33 cm (17 in)
14. Center back length to hem 58.43 cm (23 in)
15. Across front 38.59 cm (15 1/4 in)
16. Across back 40.65 cm (16 in)
17. Across shoulders 40.93 cm (16 1/8 in)
18. Side seam 33.94 cm (13 3/8 in)
19. Waist 48.63 cm (19 1/8 in)
20. Low hips 61.00 cm (24 in)


21. Blazer hemline sweep 59.50 cm (23 3/8 in)
22. Armhole length 53.94 cm (21 1/4 in)
23. Neck opening 20.91 cm (8 1/4 in)
24. Front neck drop 15.23 cm (6 in)
25. Back neck drop 4.13 cm (1 5/8 in)
26. Shoulder width 12.97 cm (5 1/8 in)
27. Apex to apex 20.85 cm (8 1/4 in)
28. Seam allowance poc max 3.00 none (1 1/8 in)
29. Hem poc max 6.00 none (2 3/8 in)
30. Pocket height 12.08 cm (4 3/4 in)

cozysewpatterns

Paper Size: A4;
Print Actual Size (100% Scale);




1
CENTER FRONT
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2




5

FRONT NECK FACING

MAIN FABRIC: Cut 2

FUSIBLE INTERFACING: Cut 2




8


BACK ARMHOLE FACING


MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2



6
FRONT ARMHOLE FACING
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2


2/1






3
CENTER BACK
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2
2/1



2
SIDE FRONT
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2
3/2








4/2





9
PATCH POCK
MAIN FABRIC: C
5/1

5/2





ET
ut 2
6/1


7
BACK NECK FACING
MAIN FABRIC: Cut 1
FUSIBLE INTERFACING: Cut 1


4
SIDE BACK
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2

6/3



7/3