
cozysewpatterns

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 119.25, Waist: 104.75, Hips: 125.75
SIZE 20

Notes



How to print

Printing

Once your Calibration Test Page has been printed, measure the 4”x 4” (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.

SIZE 20
Seam Allowance: 1 (3/8 in)

Pattern pieces:

1. "CENTER FRONT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
2. "SIDE FRONT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
3. "CENTER BACK", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
4. "SIDE BACK", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
5. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
6. "FRONT ARMHOLE FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
7. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
8. "BACK ARMHOLE FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
9. "PATCH POCKET", MAIN FABRIC: Cut 2


Pattern Specs (Circumferences are divided by 2):


1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Shoulder pads thickness 1.00 none (3/8 in)
6. Pocket entry length 12.11 cm (4 3/4 in)
7. Waist to pocket length 2.56 cm (1 in)
8. Side seam pocket position 10.31 cm (4 in)
9. Button diameter 1.50 cm (5/8 in)
10. Front buttons quantity 6.00 pc
11. Front length from HPS to hem 64.07 cm (25 1/4 in)
12. Across chest 67.78 cm (26 5/8 in)
13. Center front length to hem 44.83 cm (17 5/8 in)
14. Center back length to hem 59.04 cm (23 1/4 in)
15. Across front 47.10 cm (18 1/2 in)
16. Across back 44.29 cm (17 3/8 in)
17. Across shoulders 43.40 cm (17 1/8 in)
18. Side seam 33.45 cm (13 1/8 in)
19. Waist 60.08 cm (23 5/8 in)
20. Low hips 71.88 cm (28 1/4 in)

21. Blazer hemline sweep 70.38 cm (27 3/4 in)
22. Armhole length 59.79 cm (23 1/2 in)
23. Neck opening 22.35 cm (8 3/4 in)
24. Front neck drop 16.94 cm (6 5/8 in)
25. Back neck drop 4.22 cm (1 5/8 in)
26. Shoulder width 13.59 cm (5 3/8 in)
27. Apex to apex 24.85 cm (9 3/4 in)
28. Seam allowance poc max 3.00 none (1 1/8 in)
29. Hem poc max 6.00 none (2 3/8 in)
30. Pocket height 13.32 cm (5 1/4 in)

cozysewpatterns

Paper Size: LETTER;
Print Actual Size (100% Scale);






1

CENTER FRONT

MAIN FABRIC: Cut 2

FUSIBLE INTERFACING: Cut 2




5

FRONT NECK FACING


MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2


1/2





2/1









1
FUSIB







3

CENTER BACK

MAIN FABRIC: Cut 2


LE INTERFACING: Cut 2

4


SIDE BACK


MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2





4/2








9
PATCH POCKET
MAIN FABRIC: Cut 2
5/2




SIDE FRONT
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cu


8
BACK ARMHOLE FACING
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2
6/12
2




6


FRONT ARMHOLE FACING


MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2


6/3


ut 2




H3




7
BACK NECK FACING
MAIN FABRIC: Cut 1
FUSIBLE INTERFACING: Cut 1
8/2

8/3