
Print this Calibration Test page first!

Size: Height: 167.75, Bust: 114.25, Waist: 99, Hips: 120.75
Pattern Name: -

Notes



How to print

Printing

Once your Calibration Test Page has been printed, measure the 4”x 4” (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.

Pattern Name: -
Seam Allowance: 1 (3/8 in)

Pattern pieces:


1. "CENTER FRONT", MAIN FABRIC: Cut 2
2. "SIDE FRONT", MAIN FABRIC: Cut 2
3. "CENTER BACK", MAIN FABRIC: Cut 1
4. "SIDE BACK", MAIN FABRIC: Cut 2
5. "SLEEVE", MAIN FABRIC: Cut 2
6. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
7. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
8. "COLLAR STAND", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
9. "WELT", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
10. "INNER POCKET BAG", LINING: Cut 2
11. "OUTER POCKET BAG", MAIN FABRIC: Cut 2


Pattern Specs (Circumferences are divided by 2):

1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Stretch factor horizontal 1.00 none (3/8 in)
6. Stretch factor vertical 1.00 none (3/8 in)
7. Front neck drop 9.26 cm (3 5/8 in)
8. Pocket entry length 13.14 cm (5 1/8 in)
9. Waist to pocket length 4.79 cm (1 7/8 in)
10. Side seam pocket position 3.67 cm (1 1/2 in)
11. Pocket width welt 3.00 cm (1 1/8 in)
12. Button diameter 1.00 cm (3/8 in)
13. Front buttons quantity 13.00 pc
14. Front length from HPS to hem 104.89 cm (41 1/4 in)
15. Across chest 60.06 cm (23 5/8 in)
16. Center front length to hem 95.82 cm (37 3/4 in)
17. Center back length to hem 99.17 cm (39 in)
18. Across front 44.28 cm (17 3/8 in)
19. Across back 38.02 cm (15 in)
20. Across shoulders 41.04 cm (16 1/8 in)

21. Side seam 72.94 cm (28 3/4 in)
22. Waist 53.30 cm (21 in)
23. Low hips 65.89 cm (26 in)
24. Hemline sweep 138.08 cm (54 3/8 in)
25. Armhole length front 25.50 cm (10 in)
26. Armhole length back 31.40 cm (12 3/8 in)
27. Neck opening 16.55 cm (6 1/2 in)
28. Back neck drop 3.76 cm (1 1/2 in)
29. Shoulder width 12.70 cm (5 in)
30. Neckline length 46.51 cm (18 1/4 in)
31. Seam allowance poc max 3.00 none (1 1/8 in)
32. Pocket bag height 18.57 cm (7 1/4 in)
33. Sleeve length 58.39 cm (23 in)
34. Sleeve upper arm width 42.83 cm (16 7/8 in)
35. Sleeve opening 26.75 cm (10 1/2 in)
36. Sleeve cap length 58.55 none (23 in)
37. Stand height 3.00 cm (1 1/8 in)
38. Collar length 46.51 cm (18 1/4 in)

Paper Size: A4;
Print Actual Size (100% Scale);






3


CENTER BACK


MAIN FABRIC: Cut 1




5
SLEEVE


MAIN FABRIC: Cut 2








2/1
















MAIN FABRIC: Cut 2


EASE

10


INNER POCKET BAG


11


OUTER POCKET BAG





LINING: Cut 2









7
BACK NECK FACING
MAIN FABRIC: Cut 1
FUSIBLE INTERFACING: Cut 1


9
WELT
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2










SIDE BACK

MAIN FABRIC: Cut 2






4


2


SIDE FRONT


MAIN FABRIC: Cut 2

















6/5













7/5


8
COLLAR STAND
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2
8/1


8/2
FOLD


MAIN FABRIC: Cut 2
c/s




1

8/4

CENTER FRONT

MAIN FABRIC



6

FRONT NECK FACING


MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2


8/5

9/1

9/2










10/1

10/2

10/3







11/1

11/2

