
cozysewpatterns

Print this Calibration Test page first!

Size: Height: 157.75, Bust: 75, Waist: 62.25, Hips: 80.25
12 158

Notes



How to print

Printing

Once your Calibration Test Page has been printed, measure the 4”x 4” (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.

12 158
Seam Allowance: 1 (3/8 in)

Pattern pieces:

1. "RIGHT FRONT", MAIN FABRIC: Cut 1
2. "LEFT FRONT", MAIN FABRIC: Cut 1
3. "BACK", MAIN FABRIC: Cut 1
4. "SLEEVE", MAIN FABRIC: Cut 2
5. "LEFT FRONT BUTTON FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
6. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
7. "COLLAR", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
8. "FRONT CLOSURE FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
9. "RIGHT FRONT PLACKET", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1


Pattern Specs (Circumferences are divided by 2):


1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Stretch factor 1.00 none (3/8 in)
4. Stretch factor horizontal 1.00 none (3/8 in)
5. Stretch factor vertical 1.00 none (3/8 in)
6. Button diameter 1.00 cm (3/8 in)
7. Front buttons quantity 8.00 pc
8. Front length from HPS to hem 61.38 cm (24 1/8 in)
9. Across chest 40.00 cm (15 3/4 in)
10. Center front length to hem 51.55 cm (20 1/4 in)
11. Center back length to hem 54.90 cm (21 5/8 in)
12. Across front 28.92 cm (11 3/8 in)
13. Across back 29.55 cm (11 5/8 in)
14. Across shoulders 34.76 cm (13 5/8 in)
15. Side seam 34.48 cm (13 5/8 in)
16. Waist 48.87 cm (19 1/4 in)
17. Hemline sweep 60.55 cm (23 7/8 in)
18. Armhole length front 22.38 cm (8 3/4 in)
19. Armhole length back 22.51 cm (8 7/8 in)


20. Neck opening 17.11 cm (6 3/4 in)
21. Neckline length 46.16 cm (18 1/8 in)
22. Front neck drop 9.81 cm (3 7/8 in)
23. Back neck drop 2.96 cm (1 1/8 in)
24. Shoulder width 8.83 cm (3 1/2 in)
25. Placket length 51.55 cm (20 1/4 in)
26. Placket width 3.00 cm (1 1/8 in)
27. Collar width 9.50 cm (3 3/4 in)
28. Collar edges length 9.00 cm (3 1/2 in)
29. Sleeve length 58.28 cm (23 in)
30. Sleeve upper arm width 28.44 cm (11 1/4 in)
31. Sleeve opening 21.71 cm (8 1/2 in)


cozysewpatterns

Paper Size: LETTER;
Print Actual Size (100% Scale);




BACK
MAIN FABRIC: Cut 1
8
FRONT CLOSURE FACING
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2
1/1


1/2
3
BACK




2


LEFT FRONT


MAIN FABRIC: Cut 1





1/4




















9
RIGHT FRONT PLACKET
MAIN FABRIC: Cut 1
FUSIBLE INTERFACING: Cut 1
3/2




EASE
FUSIBLE INTERFACING: CUT 1



3/5
5
LEFT FRONT BUTTON FACING
MAIN FABRIC: Cut 1

1



RIGHT FRONT


MAIN FABRIC: Cut 1




4


SLEEVE

MAIN FABRIC: Cut 2





4/3








5/1





5/2
FOLD


FUSI








6

K NECK FACING
IN FABRIC: Cut 1
E INTERFACING: Cut 1

6/1



FOLD

7

COLLAR

MAIN FABRIC: Cut 2

BLE INTERFACING: Cut 2