
Print this Calibration Test page first!

Size: Height: 167.75, Bust: 109.25, Waist: 93.25, Hips: 115.5
Pattern Name: -

Notes



How to print

Printing

Once your Calibration Test Page has been printed, measure the 4”x 4” (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.

Pattern Name: -
Seam Allowance: 1 (3/8 in)

Pattern pieces:


1. "CENTER FRONT", MAIN FABRIC: Cut 2
2. "SIDE FRONT", MAIN FABRIC: Cut 2
3. "CENTER BACK", MAIN FABRIC: Cut 1
4. "SIDE BACK", MAIN FABRIC: Cut 2
5. "SLEEVE", MAIN FABRIC: Cut 2
6. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
7. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
8. "COLLAR", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
9. "FLAP", MAIN FABRIC, FUSIBLE INTERFACING: Cut 4
10. "WELT", MAIN FABRIC: Cut 4
11. "INNER POCKET BAG", LINING: Cut 2
12. "OUTER POCKET BAG", MAIN FABRIC: Cut 2


Pattern Specs (Circumferences are divided by 2):

1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Stretch factor horizontal 1.00 none (3/8 in)
6. Stretch factor vertical 1.00 none (3/8 in)
7. Front neck drop 9.09 cm (3 5/8 in)
8. Pocket entry length 12.83 cm (5 in)
9. Waist to pocket length 9.72 cm (3 7/8 in)
10. Side seam pocket position 9.46 cm (3 3/4 in)
11. Button diameter 1.00 cm (3/8 in)
12. Front buttons quantity 13.00 pc
13. Front length from HPS to hem 104.07 cm (41 in)
14. Across chest 57.51 cm (22 5/8 in)
15. Center front length to hem 95.17 cm (37 1/2 in)
16. Center back length to hem 98.92 cm (39 in)
17. Across front 42.40 cm (16 3/4 in)
18. Across back 37.29 cm (14 5/8 in)
19. Across shoulders 40.65 cm (16 in)

20. Side seam 73.05 cm (28 3/4 in)
21. Waist 50.36 cm (19 7/8 in)
22. Low hips 63.21 cm (24 7/8 in)
23. Hemline sweep 135.41 cm (53 1/4 in)
24. Armhole length front 25.05 cm (9 7/8 in)
25. Armhole length back 30.69 cm (12 1/8 in)
26. Neck opening 16.21 cm (6 3/8 in)
27. Back neck drop 3.72 cm (1 1/2 in)
28. Shoulder width 12.67 cm (5 in)
29. Neckline length 45.63 cm (18 in)
30. Seam allowance poc max 3.00 none (1 1/8 in)
31. Pocket bag height 13.83 cm (5 1/2 in)
32. Flap width 4.87 cm (1 7/8 in)
33. Sleeve length 58.32 cm (23 in)
34. Sleeve upper arm width 40.86 cm (16 1/8 in)
35. Sleeve opening 25.98 cm (10 1/4 in)
36. Sleeve cap length 57.25 none (22 1/2 in)
37. Collar width 9.50 cm (3 3/4 in)
38. Collar edges length 8.44 cm (3 3/8 in)

Paper Size: LETTER;
Print Actual Size (100% Scale);







3

CENTER BACK

MAIN FABRIC: Cut 1




OUTER POCKET BAG
MAIN FABRIC: Cut 2
11
INNER POCKET B
LINING: Cut 2
1/3

12


1


CENTER FRONT


MAIN FABRIC: Cut 2


MAIN FABRIC CUT 2


2/1









BAG
7
BACK NECK FACING
MAIN FABRIC: Cut 1
FUSIBLE INTERFACING: Cut 1
9
FLAP
MAIN FABRIC: Cut 4
FUSIBLE INTERFACING: Cut 4



10
WEST














3/5










SIDE BACK


MAIN FABRIC: Cut 2


5/2
4


2


SIDE FRONT


MAIN FABRIC: Cut 2




6/1













6/5

7/1













7/5


FR
FUS
8/1


8/2




SLEEVE
MAIN FABRIC:



5



6


RONT NECK FACING

MAIN FABRIC: Cut 2


SIBLE INTERFACING: Cut 2


9/2


Cut 2





9/4









FUS











C
COLLAR
MAIN FABRIC: Cut 2
SIBLE INTERFACING: Cut 2
11/2

8 11/3

FOLD



11/5



12/2

12/3

12/4

12/5